



TAL 2201 / 2202 / 2203 / 2204

# DISC PLOUGH




TAL 2201 / 2202 / 2203 / 2204



## TAFE ACCESS LIMITED

35, NUNGAMBAKKAM HIGH ROAD, CHENNAI - 600 034.  
PHONE ; 825 5217, 825 5491, 827 9073. FAX : 821 3893  
E-MAIL : tal@md3.vsnl.net.in

A subsidiary of Tractors and Farm Equipment Limited 

## FEATURES

- Hydraulically operated Implement, designed for greater strength and rigidity.
- Tubular frame construction provides high trash clearance.
- Side draft and thrust controlled by fully floating furrow wheel.
- Available in 2 Furrow, 3 Furrow & 4 Furrow units

## UTILITIES

- Suitable for use under adverse conditions like hard and dry trashy, stony or stumpy lands.
- Useful for exceptionally good lands where scouring is a major problem.

## MAIN SETTINGS

- Attach Check Strut between Right Hand side Lower Link and the implement; Ensure the length and fix properly.
- The lateral distance between the left hand cross shaft carrier bracket and the left hand shoulder on cross shaft should be 5 - 1/2" at 52" rear wheel setting and 6 - 1/2" for 56" rear wheel setting.
- The plough is set for a nominal width of cut of 11" per disc. The width of cut can be adjusted between 10 1/4" and 11 - 3/4" by rotating the cross shaft rearward and keeping the shaft on the mark (count the number clockwise viewing from the right side of the plough) provided on the cross shaft bracket.
- The annular groove on the furrow wheel axle should be set at the same number of the groove with respect to the cross shaft position. (count the groove number from free end of the furrow wheel axle.
- By rotating the spindle on the axle shaft the furrow wheel can be led either away from or into the furrow.

## SPECIFICATIONS

PARAMETERS	TAL 2201 Disc Plough	TAL 2202 Disc Plough	4 F Version
No. Of Furrows	2	3	4 (3+1)
Height (mm)	1118	1118	1118
Length (mm)	1295	1803	2310
Width (mm)	991	1118	1250
Disc Diameter (mm)	660	660	660
Furrow Width (mm)	305	305	305
Weight (kg)	236	320	460
Linkage Type	CAT I - 3 Point Linkage	CAT I & II-3 Point Linkage	CAT I & II-3 Point Linkage
Power Requirement	25 h.p & above	45 h.p & above	60 h.p & above

Ask your dealer for a demonstration



**The Metal (Pvt) Limited**

Manufacturer reserves the right to make changes in design and to add new features without obligation on machines purchased before or after such changes are made